

## ARTIFACT SHEET

Enter artifact number below. Artifact number is application number + artifact type code (see list below) + sequential letter (A, B, C . . .). The first artifact folder for an artifact type receives the letter A, the second B, etc..  
Examples: 59123456PA, 59123456PB, 59123456ZA, 59123456ZB

09728831 ZA

Indicate quantity of a single type of artifact received but not scanned. Create individual artifact folder/box and artifact number for each Artifact Type.

☐

CD(s) containing:

computer program listing

Doc Code: Computer

☐

Artifact Type Code: P

pages of specification

and/or sequence listing

and/or table

Doc Code: Artifact

☐

Artifact Type Code: S

content unspecified or combined

Doc Code: Artifact

☐

Artifact Type Code: U

☐

Stapled Set(s) Color Documents or B/W Photographs

Doc Code: Artifact    Artifact Type Code: C

☐

Microfilm(s)

Doc Code: Artifact    Artifact Type Code: F

☐

Video tape(s)

Doc Code: Artifact    Artifact Type Code: V

☐

Model(s)

Doc Code: Artifact    Artifact Type Code: M

☐

Bound Document(s)

Doc Code: Artifact    Artifact Type Code: B

☐

Confidential Information Disclosure Statement or Other Documents  
marked Proprietary, Trade Secrets, Subject to Protective Order,  
Material Submitted under MPEP 724.02, etc.

Doc Code: Artifact    Artifact Type Code: X

☒

Other, description:

Doc Code: Artifact    Artifact Type Code: Z

US Patent # 5350131 - Original

The  
United  
States  
of  
America



The Commissioner of Patents  
and Trademarks

*Has received an application for a patent  
for a new and useful invention. The title  
and description of the invention are en-  
closed. The requirements of law have  
been complied with, and it has been de-  
termined that a patent on the invention  
shall be granted under the law.*

*Therefore, this*

United States Patent

*Grants to the person or persons having  
title to this patent the right to exclude  
others from making, using or selling the  
invention throughout the United States  
of America for the term of seventeen  
years from the date of this patent, sub-  
ject to the payment of maintenance fees  
as provided by law.*

*Bence Lehman*

Commissioner of Patents and Trademarks

*Priscilla A. Keller*  
Attest



US005350131A

**United States Patent** [19]

Baumgartner et al.

[11] Patent Number: 5,350,131

[45] Date of Patent: Sep. 27, 1994

[54] **FISHING REELS WITH A SPOOL RECEIVING THE FISHING LINE**[75] Inventors: Walter Baumgartner, Theilenhofen;  
Dieter Hamann, Gunzenhausen, both  
of Fed. Rep. of Germany[73] Assignee: D.A.M. Deutsche Angelgerate  
Manufaktur Hellmuth Kuntze GmbH  
& Co. KG, Fed. Rep. of Germany

[21] Appl. No.: 788,801

[22] Filed: Nov. 7, 1991

## [30] Foreign Application Priority Data

Nov. 10, 1990 [DE] Fed. Rep. of Germany ..... 4035846

[51] Int. Cl.<sup>5</sup> ..... A01K 89/015

[52] U.S. Cl. .... 242/242; 242/43 R

[58] Field of Search ..... 242/158.1, 158.5, 43 R,  
242/241, 242

## [56] References Cited

## U.S. PATENT DOCUMENTS

2,724,563 11/1955 Shakespeare et al. .... 242/242  
4,191,343 3/1980 Morishita ..... 242/242  
5,143,318 9/1992 Tipton et al. .... 242/241

## FOREIGN PATENT DOCUMENTS

917518 1/1954 Fed. Rep. of Germany .  
944828 6/1956 Fed. Rep. of Germany ..... 242/242  
7006743 2/1970 Fed. Rep. of Germany .7007657 3/1970 Fed. Rep. of Germany .  
3417716 11/1985 Fed. Rep. of Germany ..... 242/43 R  
2264480 10/1975 France ..... 242/242  
694177 9/1965 Italy ..... 242/242  
0006497 2/1974 Japan ..... 242/43 R  
9867/87 5/1989 Rep. of Korea .  
4027/90 5/1990 Rep. of Korea .Primary Examiner—Katherine Matecki  
Attorney, Agent, or Firm—Bacon & Thomas[57] **ABSTRACT**

In a fishing reel of the type in which the spool for receiving the fishing line is caused to move to and fro in the direction of its winding axis in response to a cam drive for driving a spindle attached to the spool, the cam drive including a guide part with a guide slot into which projects an eccentrically mounted cam stud, the guide slot is in the form of an elongated S in order to impart an acceleration to the spool at its reversing points, and thereby prevent formation of bulges at the sides of the spool during winding. The locations in the guide slot corresponding to reversing points of the spool are offset from a center line of the guide slots along a longitudinal axis of the slot in a direction perpendicular to the stroke direction, resulting in the above-described acceleration and also having the effect of increasing displacement of the cam drive mechanism in the stroke direction.

6 Claims, 5 Drawing Sheets

